

# NON-REFLECTIVE FILMS

**Designed with super shrink & Anti-static property for easy installation**

*Non-Reflective Films are normal tinted films, which primarily cut the heat. Super shrink & Anti-static qualities help in easy installation.*

	CH 06 SRC	CH 20 SRC	CH 35 SRC	GREY 05 SRC	GREY 20 SRC	GREEN 70 SRC	BRONZE 15 SRC	CLEAR WEATHERABLE
Thickness	1 Mil	1 Mil	1 Mil	1 Mil	1 Mil	1 Mil	1 Mil	2 Mil
Visible Light Transmittance	6%	21%	35%	4%	22%	70%	17%	89%
Visible Light Reflectance	6%	5%	6%	6%	5%	7%	6%	6%
Solar Energy Transmittance	45%	45%	53%	41%	49%	70%	46%	81%
Solar Energy Reflectance	7%	6%	7%	6%	6%	9%	6%	6%
Solar Energy Absorbance	48%	49%	40%	53%	45%	21%	48%	13%
Ultra Violet Transmittance	< 1%	< 1%	< 1%	< 1%	< 1%	< 1%	< 1%	< 0.5%
Glare Reduction	93%	77%	62%	96%	76%	23%	81%	2%
Shading Coefficient	0.67	0.68	0.75	0.64	0.72	0.87	0.68	0.98
Emissivity	0.85	0.86	0.86	0.85	0.86	0.86	0.86	0.86
U Factor (BTU/hr./sq.ft.)	1.12	1.15	1.12	1.12	1.13	1.13	1.13	1.15
Total Solar Energy Rejection	42%	42%	36%	44%	38%	24%	41%	15%

Also available in VLTs of 35%, 50% & 70%

*Disclaimer: All values as applied to 1/8 inch Clear Plate Glass.  
Tests are representative of actual production & may vary from batch to batch.*